

DECLARATION OF PERFORMANCE No. ST-17.0

1. **Birch Plywood SVEZA PARQUET Type FSF with thickness of 9-21 mm (SVEZA PARQUET 9-21)**
2. For internal use in humid conditions (uncoated) – BS EN 636-2 NS – as non-structural components – BS EN 13986 : 2004+A1:2015 (4.5)
3. Manufacturer: **LLC SVEZA Tyumen**
Kamchatskaya str. 196, Tyumen, 625034, Russian Federation
Tel/Fax +7 (3452) 63-77-65 (2577) E-mail: vn.zablovskii@sveza.com
4. System of assessment and verification of consistency of performance of the construction product according to BS EN 13986:2004+A1:2015 – System 4
5. Declared performance:

| <i>Essential characteristics</i> | <i>Performance</i> | <i>Designated technical specification</i> |
|--|--|---|
| Bonding quality (moisture resistance) | Class 3 | BS EN 636 : 2012, BS EN 314-2:1993 |
| Release of formaldehyde | E1 | BS EN 636 : 2012, Table 3 |
| Reaction to fire | Depending on thickness and end use conditions but not less than Class D-s2, d0 | BS EN 13986, Table 8 |
| Water vapour permeability | NPD | BS EN 12524; BS EN 13986, Table 9 |
| Airborne sound insulation | NPD | BS EN 13986, 5.10 |
| Sound absorption (not valid for external use) | NPD | BS EN 13986, Table 10 |
| Thermal conductivity (by mean density of 684 kg/m ³) | NPD | BS EN 13986, Table 11 |
| Biological durability | NPD | BS EN 13986, 5.17 |
| Content of pentachlorophenol | < 5 ppm | BS EN 13986, 5.18 |
| Embedment strength | NPD | EN 13986, 5.19 |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



N.A. Gorodetsky

Director of Branch "Tyumen" of LLC SVEZA-Les

Tyumen, 30 August 2021